

NEUTRON 515

Multi-Purpose Extreme Pressure Grease

NEUTRON 515 is a formulated multi purpose grease contains selected anti friction additives, anti corrosion, anti oxidation, and extreme pressure additive, as a high quality and heavy load grease.

NEUTRON 515 use for lubricating heavy load and multi purpose bearings, trucks and passenger and transportations vehicles wheels, with operational temperature range up to 180 °C even for low and high speed.

NEUTRON 515 is recommended for all kinds of bearings, ball and roller bearings, bushings, cams, splines, universal joints, pins, bars & slides, automotive, industrial, heavy equipments, disc brake wheel bearings, coupling gears, crusher bearings, and conveyor bearings, pumps, centrifuges, blow moulding equipments, even in dry or wet condition.

TECHNICAL INFORMATION

	ASTM TEST	RESULT
N.L.G.I. Grade	D – 942	2
Penetration worked	D – 217	275 – 290
Viscosity		
@ 40 °C cSt	D – 445	285
@100 °C cSt	D – 445	21.5
Dropping Point	D – 2265	180
Flash Point	D – 92	221
Timken O.K. Load	D – 2509	45
Color	D – 1500	Red
Thickener		Lithium 12 Steared

NEUTRON FLUID & COMPOUNDS DIVISION

Value shown here are typical and may vary. NEUTRON FLUID & COMPOUNDS DIVISION reserves the right to change or modify this product for purpose of improving its performance characteristics.