



NEUTRONLUB

THE BEST HI-TECH FLUID & COMPOUNDS - USA



NEUTRON 930 Bio Biodegradable Anti Wear Hydraulic Fluid

Neutron 930 Bio offers a full line of biobased, synthetic, and mineral oil based hydraulic fluids for application in the toughest environments.

Neutron 930 Bio - Biodegradable Antiwear Hydraulic Fluids are formulated from readily biodegradable, high lubricity baseoils coupled with proprietary non-toxic antiwear and anti-corrosion additives. This high performance formula can reduce operating temperatures, friction, and component wear in mobile and industrial hydraulic systems. Excellent thermal and oxidative stability assure superior service life with minimal viscosity change over a broad range of operating temperatures. Bioflo AW fluids are suitable for use in ecologically sensitive applications or wherever areadily biodegradable, high performance antiwear hydraulic fluid is require

TECHNICAL INFORMATION.

		ASTM TEST				R E S U L T			
ISO VG			32	46	68	100			
Viscosity									
	@ 40 °C	D-445	31	44	66	109			
	@100 °C	D-445	5.2	6.7	8.8	12.2			
Gravity, @ 15,4 °C		D-287	0.840	0.846	0.865	0.955			
Flash Point, °C		D-92	118	198	202	205			
Pour Point, °C		D-97	-30	-30	-28	-28			
Viscosity Index		D-2270	111	114	115	115			
Color			Clear	Clear	Clear	Clear			

NEUTRON FLUID & COMPOUNDS DIVISION

Value shown here are typical and may vary. NEUTRON FLUID & COMPOUNDS DIVISION reserves the right to change or modify this product for purpose of improving its performance characteristics.