

NEUTRON 930 FG

Clarion Food Machinery & AW Hydraulic Oil

Neutron 930FG Clarion Food Machinery & AW Hydraulic Oil 32, 46, 68 The Food Grade Multi-Purpose Oils Have been formulated to fulfill the requirements of both Multi-Purpose and Hydraulic Lubrication in all plants. These oils possess anti-wear, anti-rust, antifoam, and anti-oxidation additives, along with a selected EP package.

Neutron 930FG Clarion Food Machinery & AW Hydraulic Oil 32, 46, 68 Oils are used in central and circulating lubrication systems, drip cups, oil cans, oil reservoirs, and all types of manual applications. They satisfy hydraulic pump antiwear demands, and rust and oxidation provisions for hydraulic systems on all types of equipment where a non-toxic lubricant is recommended or dictated!

- Extended part life
- Superior oxidation resistance
- Excellent water separation properties
- Water clear color

0

0

Multi-Purpose service!

TECHNICAL SPECIFICATION

ASTM TEST			RESULT		
ISO VG		32	46	68	150
USDA Rating		H1	H1	H1	H1
Viscosity					
@ 40 °C	D-44 <mark>5</mark>	31	45	67	158
@100°C	D-445	5.2	6.8	8.9	15.5
Gravity, @ 15,4 °C	D-287	0.840	0.846	0.865	0.955
Flash Point, °C	D-92	119	200	201	201
Pour Point, °C	D-97	-34	-34	-32	-32
Viscosity Index	D-2270	112	115	115	115
Color		Clear	Clear	Clear	Clear

NEUTRON FLUID & COMPOUNDS DIVISION

Value shown here are typical and may vary. NEUTRON FLUID & COMPOUNDS DIVISION reserves the right to change or modify this product for purpose of improving its performance characteristics.

© 1998 Copyright Reserved www.alckin.com